

STUCCO ITALIANO S.r.I

Via Rovereto 20, Costabissara 36030 - Italia T.: +39 347 2469500 - info@stuccoitaliano.it www.stuccoitaliano.com

Document:TDSCollection:20XX0Modified:19/08/2019Created:04/04/2006

## **Technical Data Sheet**

## **Liberty Epoque**

**Product description:** This highly decorative, breathable finish is for interior walls. Because of the precious metals contained in the pigment, it takes on the appearance of velvet or suede.

$\wedge$	Name:	LIBERTY EPOQUE SILVER AND GOLD
←	Composition:	Water soluble resins and metallic pigments
<b>↑</b> +5°C	Application fields:	All interior wall ceiling surfaces and interior furnishings
~ ~	Colour:	SILVER that is white which can be tinted any colour from light to dark.  GOLD that is yellowish color and can be tinted to get different gold tint and bronze effect.
\/n	Dilution:	The dilution depends on the kind of finish. It's ready to use for most applications and can be diluted up to 40%. If apply by sponge.
<u> </u>	Appearance:	Gel.
	Yield:	Its yield varies a lot depending on the kind of finish. It is 8 sq.m. per litre for a suede finish; 7 sq.m. /liter for Brocade effect and 35/sq. m. when diluted and applied with a sea sponge.
	Tools nedeed:	Metal trowels, rags, decorative rollers and marine sponges
02	Temperature for application:	Between 5 and 36° C with a humidity of less than 85%.
	Drying time:	To the touch – 2 hours at 20° C with humidity < 70% Completely - 48 hours at 20° C with humidity < 70%
	Packaging:	Plastic tubs – 1. 2.5 and 5 lit
<u></u>	Storage:	24 months if protected from freezing.
minim		



## STUCCO ITALIANO S.r.I

Via Rovereto 20, Costabissara 36030 - Italia T.: +39 347 2469500 - info@stuccoitaliano.it www.stuccoitaliano.com

## Technical Data Sheet Liberty Epoque

Safety measures:	Do not swallow. Avoid contact with eyes. Keep out of reach of children.	
Disposal:	Containers recyclable. Dispose of according to the laws in your area.	
Voc Classification:	Cat. A/I finishes for decorative effects. EU limit: 300g/I of VOC. This product contains <1.0 gr / lit.	
Specific weight:	1.14 kg / I	
pH:	$7.5 \pm 0.2$	
Vapour Permeability:	0.24 m. (max consented limit: 2 m, DIM 52 615)	
Finish Possible:	Brocade, Satin lamé, Sea Sponge, With brush	
Voc Classification:	21.31 gr/kg. EU limit: 300 gr/mg	

For application see the videos of application since they are various and very different one to the other.

The technical information and application advice given are based on the present state of our best scientific and practical knowledge, nevertheless the suggestions and advice are provided without warranty.

The company reserves the right to make modifications at any time.