

Technical Data Sheet

Liscio - Wet

Product description: Putty paste ready for use

Name: LISCIO Wet



Generality:

Putty paste for internal use, ready to use, high filling power and high performance. Allows smoothing the raw or finished walls and ceilings (surfaces of concrete, plaster and wood) fast and clean; applicable only thick thin layers stacked as it stands as supplied or with the addition of a small amount of water. It is spread with a spatula or trowel. The ease of application allows the dough smooth consumption very low. The product has a long shelf life even after opening; it can be closed and kept, in fresh place



Classification VOC (Directive 2004/42/CE):

This product has < 1gr /kg Voc



Surface preparation:

NEW SURFACES

Direct application without prior preparation, always in thin layers

ALREADY PAINTED SURFACES

Apply one coat of acrylic primer UNIVERSAL PRIMER, then proceed with shaving. Avoid thick layers.



Tips for applying:

Room temperature: min 5°C / max. 35°C Relative humidity: min. 35% / /max. 85% Conditions of surface: dry



Storage:

Keep the tightly closed in a cool, dry • Storage Temperature: more 5°C / less than 35°C • Shelf life: 18 months in optimal conditions of temperature and humidity



Safety standards:

Product free from labeling according to D. Leg.vo No. 65/03 Empty containers with traces of film of dried product should be disposed of according to local regulations



Specifications:

Data collected in the laboratory at 20°C and 65% R. Humidity

Packaging:

24 kg in plastic tub wet
 20 kg in paper beg powder



STUCCO ITALIANO S.r.l
Via Rovereto 20, Costabissara 36030 - Italia
T.: +39 347 2469500 - info@stuccoitaliano.it
www.stuccoitaliano.com

Technical Data

Liscio - Wet

Binder Nature: Lime and acrylic polymers

Specific gravity for packaging: 1.650 ÷ 1.670 g/liter

Color: White

Appearance of the product in the package: Mellow

Viscosity supply: Thixotropic

pH after storage: 9,2

Thinner: Ready to use

Type of thinner: Water (for cleaning tools)

Application system: Spatula, trowel

Yield: Variable as required (0.7 to 1.5 kg/sqm of product per layer)

Drying in surface: 2 ÷ 4 hours



STUCCO ITALIANO S.r.l
Via Rovereto 20, Costabissara 36030 - Italia
T.: +39 347 2469500 - info@stuccoitaliano.it
www.stuccoitaliano.com

Technical Data

Liscio - Wet

Range for sanding 8 ÷ 10 hours
ready to be sanded:

Re-coating: min. 12 hours/ max.10 days

Adherence: Excellent

This information is based on best technical knowledge in our possession and believed to be correct to the issue date of this news. recommendations and i the above suggestions are not a guarantee as the conditions under the terms of use our direct control. For any clarification or explanations. Our technical staff and 'always available in company.