

Technical Data Sheet

Universal Primer

Product description: Special primer for lime-based products



Name: UNIVERSAL PRIMER PRIMER FOR LIME BASED PRODUCT



Composition: Special acrylic polymer, water, special additives.

Colours: Transparent



Appearance: Opaque, slightly rough

Type of Surface to be Covered: New plaster, Gypsum, Plasterboard, Medium density wood



Old plaster washable paint: Use as a primer for Marmorino Veneziano, Lime Paint, Intonachino and all the other lime based products and to consolidated any plaster before painting.

Application: by hand with brush or roller



Packaging: 1 lit, 5 lit, 10 lit, polyethylene containers



Dilution: 600 –1000% with water. Normal dilution is 1 to 8 with water.

Theoretical Yield: 40 lit to 70 gm/lit. of dilyted product



Drying: 1 hours at 20°C (68°F) to the touch
 10 hours at 20°C (68°F) below the surface



Application Temperatures: min. 5°C (41°F) max 30°C (86°F) - R.U.< 85% ca.



STUCCO ITALIANO S.r.l
Via Rovereto 20, Costabissara 36030 - Italia
T.: +39 347 2469500 - info@stuccoitaliano.it
www.stuccoitaliano.com

Technical Data Sheet

Universal Primer

Specific weight :	1.480 ± 80 (gr/l.)
Viscosity:	thixotropic
pH after 30 days:	8,0 ± 0,20
Inflammability:	thixotropic
Shelf Life:	24 months.
Storage Suggestions:	Product maintains its characteristics best if protected from extreme heat or cold
Safety Norms:	Protect eyes. In case of contact with eyes or skin, rinse thoroughly with water. Keep out of reach of children.
Disposal:	Product must be disposed of according to norms and regulations in force. Containers must be recycled.